

## Unit Information

|                                 | Weatherproof/Food-Safe Remote Heads |            |                                 |                                 |
|---------------------------------|-------------------------------------|------------|---------------------------------|---------------------------------|
|                                 | Lamp Volts                          | Lamp Watts | Single Head with Mounting Plate | Double Head with Mounting Plate |
| Incandescent PAR-36 Sealed Beam | 6                                   | 8          | 36WP6-8                         | 36WPDH6-8                       |
|                                 | 6                                   | 18         | 36WP6-18                        | 36WPDH6-18                      |
|                                 | 6                                   | 25         | 36WP6-25                        | 36WPDH6-25                      |
|                                 | 12                                  | 18         | 36WP12-18                       | 36WPDH12-18                     |
|                                 | 12                                  | 25         | 36WP12-25                       | 36WPDH12-25                     |
|                                 | 12                                  | 30*        | 36WP12-30                       | 36WPDH12-30                     |
| Halogen PAR-36 Sealed Beam      | 6                                   | 6          | H36WP6-6                        | H36WPDH6-6                      |
|                                 | 6                                   | 8          | H36WP6-8                        | H36WPDH6-8                      |
|                                 | 6                                   | 12         | H36WP6-12                       | H36WPDH6-12                     |
|                                 | 6                                   | 20         | H36WP6-20                       | H36WPDH6-20                     |
|                                 | 12                                  | 8          | H36WP12-8                       | H36WPDH12-8                     |
|                                 | 12                                  | 12         | H36WP12-12                      | H36WPDH12-12                    |

\*Spot Pattern

## Unit Information

|                            | Recessed Remote Gimbal Fixture |            |                          |
|----------------------------|--------------------------------|------------|--------------------------|
|                            | Lamp Volts                     | Lamp Watts | Single Head with Housing |
| Halogen PAR-36 Sealed Beam | 6                              | 8          | H36GF6-8                 |

### 36WP & H36WP SERIES WEATHERPROOF/FOOD-SAFE

Single 5" PAR-36 Weatherproof Neoprene lamp housing with clear Lexan Lens Guard. Ideal for food-safe areas. Gasketed, die cast mounting plate mounts to 4" round box. Fully assembled with swivel and lead wires.

36



36WP SINGLE HEAD

### 36WPDH & H36WPDH SERIES WEATHERPROOF/FOOD-SAFE

Double 5" PAR-36 Weatherproof Neoprene lamp housings with clear Lexan Lens Guards. Ideal for food-safe areas. Gasketed, die cast mounting plate mounts to single gang box. Fully assembled with swivel and lead wires.



36WP DOUBLE HEAD

### 36GF SERIES

Remote recessed gimbal fixture with single PAR-36 sealed beam lamp. Gimbal ring adjusts to 30° in four directions. Matte white trim ring.

5.75" Diameter Finished Opening  
8.31" Diameter Trim Size  
5.75" x 4.75" D Housing Dimension

#### Option

Add Suffix to Catalog Number  
-EM Emergency Mode



36GF