

Series Features



- Choice of Light Source
LED (Indirect View) 25+ Years
- LED Models have Double LED Strips for Increased Illumination



- Triangular Shape
- Two- or Three-Face Signs Available
- 20-Gauge Steel Housing
- White Powder-Coat Finish
- Back Mount (Two-Face Signs)
- Ceiling or Pendant Mount (Three-Face Signs)
- Directional Chevron Snapouts
- Meets or Exceeds UL 924

Additional Emergency Unit Features



- Integrated Solid State System
- Constant Current, Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- AC Lockout (Line Latching)



- Sealed Lead Calcium Battery
5-Year Warranty OR
- Sealed Nickel Cadmium Battery
10-Year Warranty
- Maintenance-Free



- Test Switch
- Red (Power On & Charge) Indicator

Unit Information

Series	Light Source	Standard Voltage	Max. Input Watts (120VAC)	Max. Input Watts (277VAC)	Replacement Battery
AC Only					
TRXL	LED (Indirect)	120/277V	3.5W	3.5W	N/A
Emergency					
ETRXL	LED (Indirect)	120/277V	3.5W	3.5W	N71

Ordering Information

ETRXL	1	R	W	W	-QC
Series	# Faces	Letter Color	Stencil Color	Housing Color	Options
TRXL-AC/LED ETRXL-EM/LED	2 3	R ed G reen	W hite B lack	W hite B lack	Factory Options

TRX




Options

- Add Suffix to Catalog Number
- 277 277VAC Input
 - 2CKT (2) Independent AC Circuits

Accessories

Order Separately

- P12W 12" Pendant Kit, White*
 - P12B 12" Pendant Kit, Black*
- *Pendant Kits from 12" to 84" Available



Made in USA

