

WL



Dimensions

WL
 Height: 12.5"
 Width: 8.5"
 Depth: 6.0"

The WL Series features an enclosure that is ideal for wet locations. It is resistant to corrosive atmospheres, non-hazardous dust environments, water spray or splashing water.



Series Features



- Wet Location Emergency Light




- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating
120VAC 60Hz 5W / 277 VAC 60 Hz 5W
- Brownout Sensitivity
- Solid State Charging Circuit
- AC Lockout (Line Latching)
- Short Circuit and Overload Protection on DC Output



- High Intensity Tungsten Lamps, 6V, 7.2 Watt
- Optional 1.5W LED Bulb



- Sealed Lead Calcium Battery
- 6-Volt Operation
- Maintenance Free



- Light Grey ABS Housing
- Corrosion Resistant and UV Stabilized
- Sealed Momentary Test Switch
- Sealed AC Ready Light

Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
2WL6S8	7	18	14	9	7	-	-	-	-	(1) S68
2WL6S10	7	32	24	16	12	10	8	7	6	(1) S610SL
2WL6N7	7	18	14	9	7	-	-	-	-	(1) N67

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 48 hours.

NEC requires 1.5 hours of emergency illumination.

Ordering Information

L	2	WL	6	S	8	-20
L-LED Wedge Base	Lamp Heads on Unit	Series	DC Battery Voltage (6 - 6-Volt)	Battery Type (S-Sealed) (N-Ni Cad)	Battery AMP Hour	Options