

# Commercial Emergency Lights

## LASER



### Dimensions

LASER  
 Height: 6.5"  
 Width: 15.5"  
 Depth: 4.5"

### Options

Add Suffix to Catalog Number

- BLK Black Finish
- N Nickel Cadmium Battery
- P2 Cord & Plug for 120VAC Input
- W White Finish
- L LED

Shown in Standard Beige

The LASER emergency lights are a low-profile, steel-constructed unit, suitable for installation where unit size and cost are premium considerations.



Made in USA

### Series Features

- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating
 

120VAC	60 Hz	.20 Amps
277VAC	60 Hz	.20 Amps



- Optional LED Bulbs 1.5-Watt
- High-Intensity Tungsten Lamps, 6-Watt



- Sealed Lead Calcium Battery (Std.) or Sealed Nickel Cadmium Battery (N)
- 6-Volt Operation
- Maintenance-Free



- Slim Line Styling
- 20-Gauge Steel Housing
- Polycarbonate Lamp Enclosures
- Beige Powder-Coat Finish Standard
- Red (Power On) LED Indicator
- Test Switch
- UL Listed
- New York City Approved/Calendar #38236

### Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								
		1.5	2	3	4	5	6	7	8	
LASER	6	12	9	6	-	-	-	-	-	(1) S65

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 48 hours.

NEC requires 1.5 hours of emergency illumination.

### Ordering Information

LASER	-P2
Series	Options LED