








Plastic Diffused LED Exits & Two-Headed Combo LED Exits

Series Features

-  • 120/277 VAC Operation
-  • Maximum Input Rating (120 or 277VAC) 1.7 Watts Standard
- Light-Emitting Diodes – 25+ Year Life
- Illuminates with Uniform Color and Brightness
- Indirect Placement for Diffused Legend Output
- Ceiling, End or Back Mount
- Canopy
- Universal Stencil
-  • Directional Chevron Snapouts
- White Finish
- Easy Installation
- UL Listed
- Flame-Retardant, High-Impact, Thermoplastic Housing
- Damp Location

Additional Emergency Unit Features

-  • Integrated Solid State System
- Constant Current, Controlled Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
-  • Initial Increased LED Brightness Level in Emergency Mode
- 2EXKL: (2) 6W Adjustable Lamp Heads
-  • EXKL: Sealed Nickel Cadmium Battery
10-Year Battery Warranty
- 2EXKL: Sealed Lead Cadmium Battery
5-Year Battery Warranty
-  • Test Switch
- LED (Power On) Indicator

Ordering Information

EXKL	1	R	W	W	U	-SD
Series	# Faces	Letter Color	Stencil Color	Housing Color	Universal	Options
XKL – AC Only EXKL – Emer 2EXKL – Combo	2	<u>R</u> ed <u>G</u> reen	<u>W</u> hite	<u>W</u> hite	Single- or Double-Face	Factory Options

XKL



XKL/EXKL



2EXKL

Options

Add Suffix to Catalog Number

For 2EXKL Only

- BLK Black Housing
- RMT Remote Capability Additional 12 Watts at 6VDC for the 2DZF-PAR
- SD Self Diagnostic
- SALIDA Spanish "SALIDA" Exit Sign

Dimensions

XKL/EXKL

Height: 8.75
Width: 12.25"
Depth: 2.5"

2EXKL

With Heads on Side
Height: 10.2"
Width: 21.7"
Depth: 4.5"

With Heads on Top
Height: 15.7"
Width: 16.3
Depth: 4.5"

