LED Full Cutoff Emergency Wall Pack

- 120/277 VAC Operation
- Maximum Input Rating (120 or 277VAC) 120/277 VAC 18 Watts / 60Hz
 (8) LG SMD 4000K LED's
 - 1600 Lumens in AC Mode / 600 Lumens in Emergency Mode
 - Integral photocell Operates as a dusk to dawn luminaire in AC Mode
 - Full Cut-Off optics for Dark Sky Compliance
 - Back Wall Mount on Junction Box or surface conduit
 - Die Cast Aluminum Housing with premuim heat sink
 - Polyester Powder Coat Paint Finish
 - Bronze color standard (contact factory for other color options)
 - UV resistant polycarbonate lens
 - Suitable for Indoor or Outdoor Applications
 - Self Diagnostic Standard

Additional Emergency Unit Features

- Maximum Input Rating (120 or 277VAC)
- Integrated Solid State System
- Constant Current, Controlled Automatic Charger Circuit
 - Low-Voltage Battery Cutoff
 - Brownout Sensitivity
 - Voltage Surge Protection
 - 7.2V Nickel Cadmium Maintenance-Free Battery,
 - 5-Year Pro-Rated Battery Warranty
 - Battery Heater Standard for Cold Locations (-40°F)
 - 24 hour recharge after full discharge
 - 1.5+ Hours Illumination on Battery Power
 - Test Switch / AC on Power Indicator Light
 - UL924 Listed for Wet Locations
 - IP65 Rated
 - DLC Listed

Ordering Information

FCL	DB	-PIR
Model	Housing Color	Options
<u>FCL-EM</u> – General & Emergency Lighting	DB Dark Bronze <u>WH</u> White (non standard special order) <u>BK</u> Black (non standard special order) <u>NK</u> Nickel (non standard special order)	-PIR

FC



Shown in Standard Dark Bronze Finish

Unit operates as a dusk

integral photocell as well

to dawn luminaire with

as an emergency light

in the event of power

failure

FCL	
Height:	6.25″
Width:	9.00″
Depth:	2.50″

-PIR

Dimensions

Options Add Suffix to Catalog Number

> Passisive Infrared Motion Sensor (non stock special order)



