

The WCHL-4X washdown protection for Chicago code exit signs. The unit is designed for easy back mounting.

FEATURES

- Units Satisfy the Requirements of NEMA 1, 2, 3, 3R, 4 & 4X enclosures
- 120/277 VAC Operation
- Maximum Input Rating (120 or 277VAC)
- Standard 1.7 Watts
- Light-Emitting Diodes—25+ Year Life
- Indirect Placement for Diffused Legend Output
- Integrated Solid State System
- Constant Current, Controlled Automatic Charger Circuit
- Low—Voltage Battery Cutoff
- Brownout Sensitivity
- AC Power On LED Indicator Light
- Push to Test Button
- Sealed Nickel Cadmium Battery
- Open-Face Glass Panel
- Chicago Code Exit
- Back Mount

WARRANTY

- 10 Year Battery Warranty
- Lifetime Fixture Warranty
- Maintenance Free



WCHL-4X

The WCHL-4X provides washdown protection for city of Chicago exits

Options:

- * **SS** - Stainless Steel (Standard)
- * **STAIR**- "STAIR" Legend in Lieu of "EXIT"
- * **STAIRS**- "STAIRS" Legend in Lieu of "EXIT"
- * **HTR** - Heater (Specify 120 or 277 Volt)

DIMENSIONS

Height: 15.5"
Width: 17.5"
Depth: 7"/9"

Specify Arrow Configuration on all Open-Face Signs

Blank = No Arrow	DA = Dual Arrow	
AR = Arrow Right	ARAL = Arrow Right/ Arrow Left	
AL = Arrow Left	(Double-Face Only - 1 Arrow per Face)	

Series	Faces	Letter Color	Panel Color	Exit Housing Trim Color	Options
WCHL-4X = AC only	1 = Single Face	R = Red	W = White	W = White	-SS = Stainless Steel (Standard)
EWCHL-4X = Battery Backup					



Made in USA