


























**WCHL**

## Series Features






-  • 120/277 VAC Operation
-  • Maximum Input Rating (120 or 277VAC) Standard 1.7 Watts
-  • Light-Emitting Diodes – 25+ Year Life
-  • Illuminates with Uniform Color and Brightness
-  • Indirect Placement for Diffused Legend Output
-  • Ceiling, End or Back Mount
-  • Canopy
-  • Open-Face Glass Panel
-  • Silk Screen Letters
-  • 20-Gauge Steel Housing
-  • White Powder-Coat Finish
-  • Chicago Code Approved
-  • UL Listed

## Additional Emergency Unit Features

-  • Integrated Solid State System
-  • Constant Current, Controlled Automatic Charger Circuit
-  • Low-Voltage Battery Cutoff
-  • Brownout Sensitivity
-  • Increased LED Brightness Level in Emergency Mode
-  • Sealed Nickel Cadmium Battery
-  • 5-Year Shelf Life
-  • 10-Year Battery Warranty
-  • Maintenance-Free
-  • 3+ Hours Illumination in Emergency Mode\*
-  • Test Switch
-  • LED (Power On) Indicator

\*Longer Illumination Times Available. Consult Factory.

### Specify Arrow Configuration on all Open-Face Signs

- |  |  |   |
|--|--|---|
| Blank = No Arrow   |  | DA = Dual Arrow    |
| AR = Arrow Right  |  | ARAL = Arrow Right/<br>Arrow Left   |
| AL = Arrow Left   |  | (Double-Face Only – 1 Arrow per Face)   |

## Ordering Information

WCHL	1	R	W	W	-TP
WCHL-AC Only EWCHL – Emer.	# Faces 1 2	Letter Color Red	Panel Color White	Housing Color White* Black PM Painted Matte Chrome	Option Factory Options



### Accessories Order Separately

- 63 Wire Guard (for Single-Face Back Mount Only)
- P12W 12" Pendant Kit, White\*

### Dimensions

WCHL / WECHL  
Height: 10.75"  
Width: 13.00"  
Depth: 2.75"

### Options

- Add Suffix to Catalog Number
- TP Tamper-Proof Screws
  - STAIR "STAIR" Legend in Lieu of "EXIT"
  - STAIRS "STAIRS" Legend in Lieu of "EXIT"
  - SS Stainless Steel



Made in USA