

## Series Features



- Wet Location LED Exit Sign
- Meets NFPA Life Safety 101, NEC, OSHA, Local and State Codes



- Dual-Voltage Transformer for 120/277 VAC Operation



- LED 25+ Years



- Light Grey ABS Housing
- Corrosion Resistant and UV Stabilized
- Polycarbonate Clear Front Cover
- Removable Directional Chevrons
- UL Listed, DOE & CEC Registered

## Additional Emergency Unit Features



- Integrated Solid State System
- Brownout Sensitivity
- AC Lockout



- 2EWLXM: (2) 1.17 W Adjustable Sealed Lamp Heads
- Optional Remote Capable Version Can Offer 3 watts for 90 Minutes



- Sealed Nickel Cadmium 6V
- Maintenance Free



- Sealed Momentary Test Switch
- Sealed AC Ready Light
- Ceiling, End, Or Wall Mount

## Ordering Information

WLXM	1	R
WLXM - AC Only	# Faces	Letter Color
EWLXM - Battery & Backup	1	<u>R</u> ed
2EWLXM-Emer. Exit Combo	2	<u>G</u> reen

## WLXM



## 2EWLXM



For wet and corrosive environments. A heavy-duty gasket protected housing makes the enclosure resistant to corrosive atmospheres, non-hazardous dust, water spray, splash and even hose-downs. Ideal for industrial or other applications subject to wet or cold weather.

## Dimensions

### WLXM/EWLXM

Height: 8.25"  
Width: 12.75"  
Depth: 2.50"

### 2EWLXM

Height: 13.75"  
Width: 12.75"  
Depth: 2.50"

