

The MINI-INV series is designed to provide sinusoidal AC emergency power to connected incandescent, fluorescent, or LED fixtures of between 55 and 220 watts.

FEATURES

Input

- Input Voltages: 120 or 277VAC field selectable.
- Input Frequencies: 60Hz \pm 2%
- Input Protection: AC Line Fuses

Output

- Output Voltages: (60Hz) 120 or 277VAC
- Waveform: Sinusoidal (digitally controlled, PWM design)
- Output Frequencies: 60Hz. \pm 0.3Hz during emergency cycle
- Output Distortion: Less than 3% THD (linear load)
- Output Protection: Line and Inverter fuses

Housing

- Heavy duty steel cabinet is finished in white powder coat paint
- Surface Mount (standard) - designed for mounting to walls with key-hole slots
- Recess Mount (REC) - provide recess mounting holes on both sides of the enclosure
- T-Grid (T-GRID) - allows simple drop-in installation between T-grid runs

WARRANTY/Listing

3 Year unit warranty

3 Year battery warranty plus and additional 7 years of pro-rata coverage
UL 924



MINI-INV

The MINI-INV is designed for to provide emergency power for incandescent, fluorescent, or LED fixtures between 55 and 220watts

Options:

- * **REC** – Recessed Housing
- * **SD** - Self Diagnostic
- * **RTS** - Remote Test Switch Panel
- * **T-GRID** - T-Grid housing
- * **4CS** - 4 Output Circuit Switching

| Series | Capacity | VA Rating | Housing | Options |
|----------|-----------------------------|--------------|-------------------|----------------------|
| MINI-INV | 55W = 55 Watts (125VA Only) | -125 = 125VA | (Blank) = Surface | SD = Self-Diagnostic |
| | 110W = 110 Watts | -250 = 250VA | REC = Recessed | |
| | 220 = 220W (250VA Only) | | T-GRID = T-Grid | |

