

New York Approved Combination Exit / Light

Series Features



- 120/277 VAC Operation
- 1.5 Hours of Emergency Illumination
- Integrated Solid State System
- Constant Current, Controlled, Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Brownout Sensitivity



- Ultra-Bright, energy efficient, long-life Red LEDs
- Smooth metal reflectors and glass lens for optimal light output
- Two fully Adjustable 12 watt Light Heads With Optional Third
- K/Os provided on sides of unit to relocate lamp heads



- Sealed Lead Calcium Battery
- 6-Volt Operation (S610)
- Maintenance-Free



- Mounting hardware included for back surface wall mount
- Top & Side K/Os for conduit feed applications
- NY Compliant 8" Letters
- Directional Chevron Knockouts
- 20-Gauge Steel Housing
- High Impact Thermoplastic Lamp Enclosures
- White or Black Powder-Coat Finish
- Easy Installation
- Charge rate/power "ON" LED indicator light
- Test Switch
- UL Listed for Damp Locations

CNYX



Shown with optional third head installed



Dimensions

HOUSING

Height: 16.25"
Width: 14.50"
Depth: 5.00"



Ordering Information

3	CNYX	1	R	W	W	-U
Emergency Light	Series CNYX	# Faces 1	Letter Color Red	Stencil Color White Black	Housing Color White Black	Options Factory Options
3 - Standard 0 - No Heads						